



SHT Liquid Sampler

Gas-tight liquid sampling device. The transfer of liquid sample to laboratory bottle done under closed condition.

PRODUCT SPECIFICATION

- Maximum tank overpressure, 0.3 bar
- Zone Sampling Bottle, 0.43L (430ml)
- Stainless Steel 30 meter Tape
- 2" quick connection coupling
- Weight, 8.1kg
- Dimension, 350mmW x 160mmD x 990mmH



SHT DIP

Gas-tight version dipping rod designed to penetrate sediments on tank bottom, is attached with 580g stainless steel rod and stainless steel 30m tape.

PRODUCT SPECIFICATION

- Stainless steel rod, 580g
- 30 meter Tape, metric/imperial
- 1" quick connection coupling
- Weight, 4.6kg
- Dimension, 300mmW x 160mmD x 640mmH



SHT Deck Pressure Gauge

Rugged high precision gauge provides reliable reading within the range of -10kPa vacuum and 30kPa pressure.

PRODUCT SPECIFICATION

- Pressure reading -10kPa to 30kPa
- 1" quick connection
- Thick rubber rim
- Weight, 1.5kg



SHT Gas Sampler

Designed to sample inert gas over full tank height.

PRODUCT SPECIFICATION

- 30m tube
- On/off valve
- Hollow stainless steel weight
- 1" quick connection coupling
- Weight, 2.9kg
- Dimension, 300mmW x 120mmD x 500mmH

SHT Deck Valve

SHT Deck Valve is a specialized connecting valve for tanker, oil and chemical vessel, which can be used for quick connecting portable measuring equipment such as ullage temperature interface detector, liquid/gas sampler, tank pressure gauge, etc.

PRODUCT SPECIFICATION

- Stainless steel 316 body
- PTFE valve seal
- 1", 2" quick connection
- Flange connection: JIS 5K 50A/80A, DN25/DN50, PN10
- Weather cap



Distributed by:

**The information is subject to changes without further notice.*



Sea Hover Technologies Pte Ltd

Address: 48 Toh Guan Road East, #04-154/155
Enterprise Hub, Singapore 608586



Tel: +65 6267 8061
Fax: +65 6267 8062



Email: sales@seahover.com
Website: <http://seahover.com>

www.seahover.com